




EXCLUSIVE PRODUCT WARRANTY
WARRANTY CERTIFICATE & FLOOR MAINTENANCE GUIDELINES

ASHFORD FORMULA

For Technical Support, call 1.800.998.5664



**CRETE
CLEAN**
WITH SCAR GUARD
PLUS+



ne TLC

CURECRETE DISTRIBUTION, INC.

20-YEAR PRODUCT & 5-YEAR APPLICATION WARRANTY

Complete warranty details provided on the reverse side of this certificate.

PROJECT INFORMATION

Owner:

Building Name:

Building Location:

ft² / m²:

APPLICATION INFORMATION

Invoice:

Drum Numbers:

Applicator:

Applicator Address:

Representative /
Int'l Distributor:

DATE WARRANTY ISSUED



JERALD W. JONES
PRESIDENT OF CURECRETE DISTRIBUTION, INC.



ASHFORDFORMULA.COM | 1.800.998.5664



THE WORLD LEADER IN CONCRETE DENSIFICATION

20-YEAR PRODUCT & 5-YEAR APPLICATION WARRANTY

PRODUCT WARRANTY

For a period of twenty (20) years, commencing the date on which the concrete surface described herein is treated with the Ashford Formula, Curecrete Distribution, Inc. warrants to the owner that after the specified sealing and hardening period, the treated surface will remain water-repellant, dustproof, hardened and abrasion resistant. In the event any area of the treated surface fails to remain water-repellant, dustproof, hardened and abrasion resistant, Curecrete Distribution, Inc. will, at its own expense, supply sufficient Ashford Formula to retreat any such defective area.

CONDITIONS

This Product Warranty is only effective when the Ashford Formula is correctly applied to properly prepared, cured and structurally sound concrete surfaces, and is void if structural faults occur due to faulty workmanship, improper design or cracking, or failure of materials other than the Ashford Formula.* Upon notification by the owner of any failure of the surface to perform as warranted herein, the owner must grant Curecrete Distribution, Inc. access to the surface during normal business hours. This warranty is void if the Ashford Formula treated surface is subjected to abnormal use or abuse, or is impaired by any alteration made to the surface without the warrantor's written approval, including treatments done to the surface by anyone other than a representative of Curecrete Distribution, Inc.

APPLICATION WARRANTY

For a period of five (5) years commencing the date on which the concrete surfaces described herein is treated with the Ashford Formula, and after the specified sealing and hardening period, the applicator noted on the accompanying certificate warrants to the owner that should any area of the treated surface fail to remain water-repellant, dustproof, hardened and abrasion resistant, the applicator will, at its own expense, re-treat any such defective area.

CONDITIONS

This Application Warranty applies to the application of the Ashford Formula to properly prepared and structurally sound concrete surfaces only, and is void if structural faults occur due to faulty workmanship, improper design or cracking and failure of materials other than the Ashford Formula.

LIMITATIONS

Curecrete Distribution, Inc. and the applicator of record shall not be liable in any respect for any damage to the building described herein; contents, other property or persons; nor will it be liable for any incidental or consequential damages, whether based upon negligence or otherwise. The provisions of this warranty shall constitute the owner's exclusive remedy, and will not be deemed in force until all the financial obligations to Curecrete Distribution, Inc., under all invoices relating to the product described below have been paid in full.

*Cause of deficiencies may include but are not limited to:

Excessive clay or silt in the concrete, premature floating and troweling, carbon dioxide from open heaters or internal combustion engines, vapor condensation on the surface of the concrete that is troweled or floated into the concrete, dry heat concentrated on the concrete surface, portland cement or sand shaken onto the concrete surface to absorb moistures, excessive water in the mix or added water during finishing, long distance pumping, improper spacing of saw cuts/control joints, untimely saw cutting, untimely application of wet cure or curing agent and freezing of the concrete surface.

DRUM NUMBERS